



ANSI
S3.19

NRR
32
dB

- Tapered bullet shape foam for easy insertion and removal
- Low pressure, self-adjusting foam offers long wearing comfort and quick recovery time
- Noise reduction rating (NRR): 32 dB
- Each pair individually wrapped
- Uncorded

 **WARNING:** Cancer & Reproductive Harm
- www.P65Warnings.ca.gov

TECHNICAL INFORMATION

International Standards	ANSI S3.19
Color	Orange
Sizes Available	One Size
Material	Polyurethane foam
Hearing Style	Uncorded, Foam
dB	32
Length	28mm
Width	12mm
Packaging	1 pair / polybag
Packed	200 polybags / box 10 boxes / case
Applications	Food Processing, Manufacturing
Registration Number	78713
Country of Origin	Taiwan
Harmonization Code	3926.90.9985

INFORMATION REQUIRED BY EPA:

The level of noise entering a person's ear, when a hearing protector is worn as directed, is closely approximated by the difference between the A-weighted environmental noise level and the NRR.

Example:

1. The environmental noise level as measured at the ear is 92 dBA.
2. The NRR is 33 decibels (dB).
3. The level of noise entering the ear is approximately equal to [92 dB (A) -33] 59 dB (A).

CAUTION: For noise environments dominated by frequencies below 500 Hz the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in attenuating noise. Consult the enclosed instructions for proper fit. Although hearing protectors can be recommended for protection against the harmful effects of impulsive noise, the Noise Reduction Rating (NRR) is based on the attenuation of continuous noise and may not be an accurate indicator of the protection attainable against impulsive noise such as gunfire.